


Rich expression with high-resolution 256 × 64 matrix for text and graphics



Customer Display

## DM-D500

ESC/POS®



for POS systems

A close-up of the EPSON DM-D500 Customer Display showing a menu with text and graphics. The text on the screen includes: "59 0.90 WHOLE WHEAT BREAD", "1.9 1.50 FRENCH BREAD (BIG)", "1.9 1.26 BLUEBERRY JAMS", "1.9 1.50 REC. PARMESAN CHEESE", "1.9 1.05 REC. BUTTER", "TAX 95.00%", "4.50", "1.50", "2.26", "3.00", "12.57", "0.63", "13.20", and "119".

59	0.90	WHOLE WHEAT BREAD	4.50
1.9	1.50	FRENCH BREAD (BIG)	1.50
1.9	1.26	BLUEBERRY JAMS	2.26
1.9	1.50	REC. PARMESAN CHEESE	3.00
1.9	1.05	REC. BUTTER	1.05
		TAX 95.00%	12.57
			0.63
			13.20
			119

A close-up of the EPSON DM-D500 Customer Display showing a menu with text and graphics. The text on the screen includes: "TABLE No. 3 家庭明 費 \*\*\* 12:07", "TABLE No. 5 家庭明 費 \*\*\* 12:13", "TABLE No. 5 家庭明 費 \*\*\* 12:13", and "TABLE No. 1 家庭明 費 \*\*\* 12:18".

TABLE No. 3	家庭明	費 ***	12:07
TABLE No. 5	家庭明	費 ***	12:13
TABLE No. 5	家庭明	費 ***	12:13
TABLE No. 1	家庭明	費 ***	12:18



Wrapstand



Checkout



Hospitality



# Express Yourself Clearer communication Means Success

Introducing the new ultimate  
in POS customer displays, the DM-D500.

## Customer Display **DM-D500**

### *For POS systems*

The EPSON DM-D500 has a variety of functions to satisfy the latest POS system demands, increasing the expressiveness of the display to make your communication with customers more attractive.

## 256 x 64 Dot Matrix Display

The full display area of the DM-D500 is 256 dots horizontally by 64 dots vertically, making a rich array of expression possible, including bit map graphics and kanji characters.



## Highly Reliable and Energy-Saving

In addition to outstanding reliability, the DM-D500 has an energy-saving function.

## 20 columns x 2 lines Mode Available

By choosing the 20 columns two line mode, it is possible to display 20 columns x 2 lines.

## Clear, Easy to Read

The display is clear and easy to read. The up/down, left/right adjustability assures optimum viewing angle.



## Displays up to Eight Lines

The resolution of the 256 x 64 dot display allows the DM-D500 to display up to eight lines. A variety of services can be performed on the DM-D500, including the display of different currencies, such as the DM and the Euro.



## Asian Language Ability

The DM-D500 can handle the Simple Chinese and Japanese languages. Customers get clear information from the high-resolution display.




## From 2400 to 115200 bps

## Design and color match EPSON TM series.

## Graphic Display

Graphic display, such as pictures and illustrations, is also possible. This function is very useful for advertisements, such as notices of current campaigns and recommended products. In addition, text and graphics can be scrolled horizontally or vertically.



## ESC/POS® Compliant

It is easy to make and to display graphics by using ESC/POS control commands, and you can register Kanji and other user characters by downloading.

## OLE POS Compatible

Compatible with OCX driver software for application development support in Windows® 95/98/NT® environments.




ESC/POS is a registered trademark of SEIKO EPSON CORPORATION. EPSON is a member of OPOS committee. Windows is a registered trademark of Microsoft Corporation.

## Four Types of Stands (optional)

Four types of stands are available: externally and internally attached stands for TM printers and stands for the TM-H6000/U675, and the IR Series. Users may choose the stand that best suits their environment.


\* A Forked pole simultaneous connection of two DM-D500s is being developed.



# Customer Display

## DM-D500

### APPEARANCE / SPECIFICATIONS



<b>Case color</b>	ECW (EPSON Cool White)
<b>EMC standards</b>	VCCI class A, FCC class A, CE marking
<b>Safety standards</b>	UL / USA / TÜV (EN 60950)
<b>Power supply</b>	PS-170

<b>Display method / color</b>	Vacuum fluorescent display / Green
<b>Resolution</b>	256 X 64 full dot matrix / 42 columns X 8 lines max. (5 X 7)
<b>Brightness</b>	300 cd / m <sup>2</sup>
<b>Buffer</b>	Receive 4K bytes / Macro 2K bytes
<b>Character type</b>	95 Alphanumeric characters / 37 International characters Graphic characters: 128 X 12 pages, kanji characters
<b>Character font</b>	5 X 7 dot matrix, 8 X 16, 16 X 16 dot matrix
<b>Euro symbol</b>	Supported
<b>Dot pitch</b>	0.55 X 0.55
<b>Download characters</b>	132 / 94 characters (Kanji gaiji)
<b>Interface</b>	RS-232
<b>Connection</b>	Pass-Through-Function* type / Direct connection
<b>Baud rate</b>	2,400~115,200 bps
<b>Reliability MTBF</b>	30,000 hours
<b>Power / current consumption</b>	12~48 VDC / Approx. 6W
<b>Overall dimensions</b>	213(W) X 51(D) X 83(H) mm
<b>Weight</b>	Approx. 460g

Notes; \* = Available with the baud rate 2,400~38,400 bps as displaying 20 columns X 2 lines.

### OPTIONAL STANDS

	Stand alone model	TM series extremely enabled	TM series extremely enabled	For Intelligent Register IR series
<b>Overall dimensions (External)</b>	200(W)X 118(D) X 65(H) mm	164(W)X 78(D) X 382 MAX(H) mm	50(W)X 53(D) X 369 MAX(H) mm	50(W)X 53(D) X 250 MAX(H) mm
<b>Weight</b>	Approx. 440g	Approx. 340g	Approx. 190g	Approx. 135g
<b>Available Models</b>	TM-T88 II / U200 Series	TM-H6000 / U950 / U675 / NT Series	TM-H5000 II / J8000	IR



### Pass-Through Function

Thanks to a pass-through function, the DM-D500 can control the printer.

※Use the interface practically.

### Direct Connection

Easy to connect with EPSON TM series of POS equipment and directly connect to your existing host terminal (serial port with a 12 V power supply required).



The Type A and Type B interface boards are connectable to DM-D500. If your printer\* has Type C interface board, please contact your nearest EPSON dealers to replace the Type C interface board with Type A or Type B interface boards.

\*TM-H5000 / H5000 II / U950 / H6000 / U675 / T285 / J8000

Specifications are subject to change without notice.

### OPTIONS

#### POWER SUPPLY



**PS-170**  
INPUT: 100~240V AC  
OUTPUT: 24 VDC, 2.0 A  
Plug: 3P Power jack  
Safety standards:  
UL, CSA, TÜV

#### POLE UNIT



**DP-105**  
254 (H) X dia.35mm